



## Features & Options

- Detection Within 5 Seconds with Local LED Alarm Indication
- Alarm Output, Two 5 Amp Relays
- Rope Detects Water Along Its Entire Length
- Automatic or Manual Unit Reset

The Water Leak Detector is designed to sense the presence of water and alert a central monitoring system of the potentially destructive situation.

Upon water detection, the alarm output relays change state, and a local red LED illuminates. The sensor detects dirty and purified water, deionized water, distilled water and reverse osmosis (RO) water.

Water Leak Detector with Rope Sensor



## Rope Sensor Mounting Bracket

The BAPI Rope Sensor Mounting Bracket is specifically designed to hold the rope taut and prevent rope slippage allowing for maximum contact with the monitored surface. Bracket can be easily mounted to flat surfaces utilizing the industrial adhesive backing or the built in screw holes.

**Part Number: BA/LDT-RR-MB (Pack of 25)**

ANOTHER ORIGINAL  
BAPI



## Specifications

### Power:

24VAC/VDC  $\pm 10\%$ , 3.9VA max @ 24VAC, 90mA max @ 24VDC (Reverse Polarity Protected)

Note: This unit does not require a separate isolated power supply.

**Rectification:** Half Wave

### Wiring:

Screw Terminals: 2 to 4 pair of 12 to 22AWG (BAPI recommends 16 to 22AWG).

Rope Sensor: 2 wires (provided), optional Flex Connector or Liquid Tight Fitting for strain relief

### Rope Sensor Specifications:

Plenum-rated sensor cable, detects 1/8" of water. Max length: 100' (30.5m)

**Alarm Reset Action:** Field selectable for Auto (Non-Latching) or Manual (Latching)

**Local Indication:** One green power LED, one red alarm LED

**Alarm Relay Contacts:** Two SPDT, 5 Amp relay outputs

### Operating Environment

Rope Sensor: 32 to 167°F (0 to 75°C)

Detector (BB): -4 to 158°F (-20 to 70°C), 0 to 95%RH, non-condensing

### Enclosure Material and Ratings:

NEMA 4 (IP66), UV-resistant polycarbonate, UL94 V-0

### Agency:

CE 61326-1:2013 EMC (Industrial Electromagnetic Environment), RoHS, UL

**Warranty:** 5 years





## Water Leak Detector Option Selection Guide

BA/ ( #1 ) - ( #2 ) - ( #3 )

**#1: Leak Detector Transmitter (required)**

LDT4..... Water leak detector with two 5A relays, SPDT contacts

**#2: Probe Sensor (required)**

RR10 ..... Remote Rope Sensor with 10 foot plenum-rated sensor cable

RR25 ..... Remote Rope Sensor with 25 foot plenum-rated sensor cable

RR50 ..... Remote Rope Sensor with 50 foot plenum-rated sensor cable

RR100 ..... Remote Rope Sensor with 100 foot plenum-rated sensor cable

**#3: Enclosure and Fitting Options (required)**

BB..... BAPI-Box enclosure, IP66 rated

BB-LTF ..... BAPI-Box enclosure, IP66 rated, with liquid tight fitting

BB-GFF ..... BAPI-Box enclosure, IP66 rated, with lex connector

**Example Number:** BA/ ( LDT4 ) - ( RR10 ) - ( BB )

**Actual Number (with parenthesis removed):** BA/LDT4-RR10-BB

**Description:** Detector with Two 5A Relays, 10' Remote Rope Sensor and BAPI-Box Enclosure

**Your Number:** BA/

## Replacement Sensors and Mounting Brackets

**Part Number**

**Sensor Type**

BA/RR10 ..... Remote Rope Sensor with 10 foot plenum-rated sensor cable

BA/RR25 ..... Remote Rope Sensor with 25 foot plenum-rated sensor cable

BA/RR50 ..... Remote Rope Sensor with 50 foot plenum-rated sensor cable

BA/RR100 ..... Remote Rope Sensor with 100 foot plenum-rated sensor cable

BA/LDT-RR-MB.. Mounting Bracket for Rope Sensor (Pack of 25)

Gray shaded items follow the Buy and Resale Multiplier.

## Dimensions

