

# ZR32K5E-TF5

HCFC, R-22, 60Hz, 3- Phase, 200/230 V

Air Conditioning



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Performance

Evap(°F)/Cond(°F)	45 / 130	50 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	70.0 / 85.0
Capacity (Btu/hr)	32600	42600
Power (Watts):	2910	2020
Current (Amps):	8.70	6.65
EER (Btu/Wh):	11.20	21.10
Mass Flow (lbs/hr):	477	545
Sound Power (dBA):	68 Avg	73 Max
Vibration (mils(peak-peak)):	2.0 Avg	3.0 Max
Record Date:	2014-03-06	

## Mechanical

Number of Cylinders:	0	Displ(in <sup>3</sup> /Rev):	2.69
Bore Size(in):	0.00	Displ(ft <sup>3</sup> /hr):	326.91
Stroke(in):	0.00		
Overall Length (in):	9.50	Mounting Length (in):	7.50
Overall Width (in):	9.50	Mounting Width (in):	7.50
Overall Height (in):	15.86	Mounting Height (in):	16.08 *
Suction Size (in):		3/4 Stub	
Discharge Size (in):		1/2 Stub	
Oil Recharge (oz):		19	
Initial Oil Charge (oz):		25	
Net Weight (lbs):		49.1	
Internal Free Volume (in <sup>3</sup> ):		118.0	
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

## Electrical

LRA-High*:	73.0	MCC (Amps):	16.8	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	19-Nov-2009
LRA Low*:		Max Operating Current:	12.0		
RLA(=MCC/1.4;use for contactor selection):			12		
RLA(=MCC/1.56;use for breaker & wire size selection):			10.8		
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

## Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	50	3	200/220	Air Conditioning
R-407C HFC	50	3	200/220	Air Conditioning
R-407C HFC	60	3	200/230	Air Conditioning