



Functional Devices, Inc.™ **Bulletin B537**

• RIBME2401SB 393020B

Functional Devices, Inc.
101 Commerce Drive
Sharpsville, IN 46068
Phone: (800) 888-5538

LED ON = RELAY ACTIVATED
www.functionaldevices.com

CONTACT RATINGS

20A Res. @ 277 Vac
1 HP @ 120 Vac
2 HP @ 277 Vac
20A Ball. @ 120/277 Vac (N/O)
10A Ball. @ 120/277 Vac (N/C)
16A Elect. Ball. @ 277 Vac (N/O)
10A Tung. @ 120 Vac (N/O)
770 VA Pilot @ 120 Vac
1110 VA Pilot @ 277 Vac

CONTROL INPUT
3mA max. @ 5-25Vac/dc



POWER INPUT

47mA @ 30Vdc
83mA @ 24Vac
47mA @ 120Vac






TYPE F, G, EM
For use with
Smoke Control
System
General Signaling
Equip. NM

SIGNALING
 **US**
LISTED
13CY
15M6

Connect Yellow Jumper Wire

N/O  to N/O or N/C  N/C

FOR SUPPLY CONNECTIONS USE
14 AWG OR LARGER WIRES
RATED AT LEAST 75°C (167°F).

- CONTROL INPUT**
-  Common
 -  5-25 Vac/dc
 -  Common
- POWER INPUT**
-  24 Vac/dc
 -  120 Vac

COIL



CONTACTS

Relay Contacts

Not Used

- 
- 
- 