



Functional Devices, Inc.™ **Bulletin B551**

• RIBME2402SB 393032B

Functional Devices, Inc.
101 Commerce Drive
Sharpsville, IN 46068
Phone: (800) 888-5538

LED ON = RELAY ACTIVATED
www.functionaldevices.com

CONTACT RATINGS

20A Res. @ 277 Vac
1 HP @ 120 Vac
2 HP @ 277 Vac
20A Ball. @ 120/277 Vac (N/O)
10A Ball. @ 120/277 Vac (N/C)
16A Elect. Ball. @ 277 Vac (N/O)
10A Tung. @ 120 Vac (N/O)
770 VA Pilot @ 120 Vac
1110 VA Pilot @ 277 Vac

CONTROL INPUT
3mA max. @ 5-25Vac/dc



POWER INPUT

47mA @ 30Vdc
83mA @ 24Vac
69mA @ 208-277Vac






TYPE F, G, EM
For use with
Smoke Control
System
General Signaling
Equip. NM

SIGNALING
 **US**
LISTED
13CY
15M6

Connect Yellow Jumper Wire

N/O  to N/O or N/C  N/C

FOR SUPPLY CONNECTIONS USE
14 AWG OR LARGER WIRES
RATED AT LEAST 75°C (167°F).

- | | | |
|---------------|---|-----------------------|
| CONTROL INPUT |  | <u>COIL</u>
Common |
| |  | 5-25 Vac/dc |
| POWER INPUT |  | Common |
| |  | 24 Vac/dc |
| |  | 208-277 Vac |



CONTACTS

Relay Contacts

Not Used

