



Defrost Thermostats

MARS SERIES **330**

COMPONENT



33008

For Defrost Termination

MARS Series 330 defrost controls are designed to replace many defrost thermostats. The leads are of sufficient length for the connection to be made at the same location as was the control removed. The connection should be insulated in a manner similar to that on the original equipment.

The selection of the proper thermostat can be made by matching the temperature code of the thermostat removed to the code on the MARS Thermostat.

Features:

- Refrigerators, A/C units, & heat pumps, dehumidifiers, icemakers or any place where a fixed temperature control is required in a wet or dirty environment.
- Thermostats have 32" leads.

MARS NO.	TEMPERATURE CODE	OPENING TEMP. F°	CLOSING TEMP F°
33008	L45	45	25
33010	L55	55	35
33011	L60	60	40
33012	L70	70	50
33020	L80	80	60

Temperature Selection Guide

TEMP. CODE	USE MARS NO.	TEMP. CODE	USE MARS NO.	TEMP. CODE	USE MARS NO.
L40-3.0	33008	L58-4.3	33011	L65-4.0	33012
L42-2.0		L60-2.0		L67-4.2	
L45-3.0		L60-2.5		L70-4.0	
L45-3.0		L60-3.0		L75-5.0	
		L60-3.5			
L55-1.5	33010	L60-4.0	33020	L80-3.0	
L55-2.0		L60-4.5		L80-4.0	
L55-2.5				L80-4.5	
L55-3.0				L80-5.0	
L55-3.5					
L55-4.0					

VOLTS	INDUCTIVE	
	F.L.A.	L.R.A.
120	5.8	25
240	2.9	70



33101

MARS Freeze Stat

The MARS 33101 is designed to help stop flood back to compressor crankcases caused by low ambient temperatures.

Features:

- Simple to install
- Refrigerators, freezers, A/C, food dispensing equipment
- 24" leads.

MARS NO.	OPENING TEMP. F°	CLOSING TEMP F°
33101	34	45

