

Condensate Pumps



Suitable for use with condensate from high efficiency condensing furnaces and boilers which produce acidic condensate. 22 feet of lift, compared to the typical 20 feet. Features include vibration dampening feet and motor mounts, metal hang tabs, four versatile inlet holes, an easy to understand indicator display, a simple float switch and check valve, and a pan pill dispenser. Integrating the CP-22 into your system is easy. 1/4" inch quick connect terminals provide easy connection to the built in overflow switch. Three terminals are provided allowing the installer flexibility to connect air-handler shut-down and optional alarm as needed. Switch features SPDT isolated contacts ready for connection to building automation systems.

- Continuous duty 140F°.
- Maximum inlet temperature 160F°.
- Not suitable for contact with steam or gasses that exceed 160F°.



CP-22 Condensate Pump

The CP-22 pump is available in both 120 and 230 volt models to accommodate any installation. Its also available with 20' of 3/8" clear tubing to facilitate even quicker setup for those on a tight schedule.

CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE	LIST PRICE
CP-22	Condensate Pump – 120V	EA	6	\$105.24
CP-22T	Condensate Pump – 120V w/20' 3/8" Tube	EA	6	\$110.88
CP-22-230	Condensate Pump – 230V	EA	6	\$127.64
CP-22-230T	Condensate Pump – 230V w/20' 3/8" Tube	EA	6	\$132.12

CP-22LP Condensate Pump



The newest addition to the CP-22 family is the LP. The CP-22LP comes packed with all the same great features found in the CP-22, but now in a low profile package. This pump is only 4-3/8" tall, so it's a good fit for those instances where space is at a premium. The shorter reservoir holds 1/3 gallon.

CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE	LIST PRICE
CP-22LP	Condensate Pump – 120V – low profile	EA	6	\$120.88