

Specifications

Product	DiversiTech Pull-out Disconnect Switches: DDS-30 , DDS-60 (fusible), and DDS-60U (non-fusible)
Application	HVAC circuitry
Power Rating	30A (DDS-30) or 60A at 240VAC, 10 horsepower max
Indoor/Outdoor Use	indoor/outdoor
Package Medium	Metal case with 180 degree opening door
Advantages	Convenient design allows for easy access to controls via wide-opening, reversible door with full dead front. Fused models benefit from having fuses located in easy pull-out handle with indicator lights for blown fuses. Line, load, and ground terminals aligned for easy wiring. EDS-60U Low-profile model also available for tighter spaces.
Directions	Please refer to an electronic copy of this product's brochure at www.diversitech.com/literature/lit-fly-disc.pdf
Safety Data	Consult the <i>Material Safety Data Sheet</i> before using these products.
HAZMAT Hazard	None.



Package Metrics

Producer of Goods	DiversiTech
Domestic/Foreign Commodity	Foreign

SKU Specific Package Metrics

UPC	DDS-30 - 095247082445 DDS-60 - 095247082452 DDS-60U - 095247082421
Unit Dimensions	DDS-30 - 2 5/8"L x 5"W x 7 1/2"H DDS-60 - 2 3/4"L x 5 1/8"W x 8 5/8"H DDS-60U - 2 3/8"L x 5"W x 7 1/2"H
Unit Weight	DDS-30 - 2.7 lbs. DDS-60 - 3.3 lbs. DDS-60U - 2.5 lbs.
Case Dimensions	DDS-30 - 14"L x 11"W x 8 1/4"H DDS-60 - 16"L x 11"W x 9 1/4"H DDS-60U - 13"L x 11"W x 8 1/4"H
Case Weight	DDS-30 - 28.6 lbs. DDS-60 - 33.7 lbs. DDS-60U - 26.6 lbs.
Quantity per Package	10



Pull-out Disconnect Switches