

Clears Condensate Drains with a SWOOSH!



Charles Gallo Drain Gun



L-99

GG-1



Clears Condensate Drains with a SWOOSH!

INSTRUCTIONS:

- 1. Unscrew the cup. Insert cartridge with the narrow end up.
- 2. Without depressing the trigger, screw the cup slowly into the head until the cartridge begins to contact the puncture pin.
- Quickly and firmly screw the unit together to puncture and seal the cartridge in the same motion.

 NOTE: Not completely screwing the unit together may result in escaping gas.
- 4. Release red safety catch.
- 5. Depress lever to discharge the SWOOSH drain cartridge. For condensate drains, a quick and full discharge is best.

SAFETY INFORMATION

WARNING: CONTENTS UNDER PRESSURE

Do not open Charles Gallo Drain Gun until cartridge is empty or injury may occur. Completely discharge cartridge before opening. Keep cartridge out of direct sunlight and temperatures above 120°. Do not discharge towards face or body.

KEEP OUT OF REACH OF CHILDREN

SWOOSH drain cartridges are Earth friendly. The gas used in our recyclable cylinders is carbon dioxide — commonly found in the atmosphere.

For use on drain lines $3/4^{\prime\prime}$ or smaller diameter, or other industrial cleaning applications.

FOR PROFESSIONAL USE ONLY

US Patent No. 6,843,388

800-995-2222 www.diversitech.com

W9385 DOC31894





