


## Refrigeration Condenser Fan 5.0" and 5.6" Diameter Open Drip Proof, Totally Enclosed, Air Over and Open Air Over



### APPLICATIONS:

Condenser cooling fan motors to meet manufacturer's requirements for commercial refrigeration units.

### FEATURES:

- OEM Direct Replacements
- Single Speed
- Automatic Reset Thermal Overload Protector
- Designed for use with 370V Capacitors
- **Discount Symbol: DS-3HAC**




Figure A




Figure B

### 5.0" Diameter, 5/16" Diameter Shaft

HP	RPM	Voltage	Catalog Number	List	Bearings	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Shaft Dia.	Mount	Ship Wt.	Notes	OEM
1/20	1500	230	1775P	\$148	SAB	3.0	.5	3.1	3.8	6.9	5/16"	Stud	8.8	98, 64	TE
1/15	1500	230	1779P	\$154	SAB	3.0	.62	3.1	3.8	6.9	5/16"	Stud	8.8	98, 64	TE

### 5.6" Permanent Split Capacitor

HP	RPM	Voltage	Catalog Number	List	Bearings	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Mount	Ship Wt.	Notes	OEM
1/6	1550	208-230	6128	\$263	SAB	5.0	0.9	2.5	4.1	7.7	Resilient	9	98, 64, H36	CO
	1550	208-230	1645	\$263	Ball	3.0	1.4	2.1	3.8	6.4	Stud	12	H35	HU
	1550	460	1265	\$248	SAB	3.0	0.55	3.1	4.1	7.1	Stud	9	98	CO
1/5	1075	208-230	1648	\$244	Ball	4.0	2.0	2.5	4.3	7.9	Stud	12	H35	HU
	1075	575	1093	\$246	Ball	4.0	.80	2.5	4.8	8.4	Stud	13	H36	
1/4	1550	230	6124	\$242	SAB	5.0	2.1	3.0	4.1	7.1	Band	13	64, H36	CO
	1625	208-230	6129	\$273	SAB	5.0	1.5	2.5	4.3	7.9	Resilient	15	64, H36	CO
	1625	230	3042	\$239	Ball	4.0	1.4	1.5	5.1	7.7	Hub Ring	15	64, H4, H36	TY
	1625	230	8330	\$241	SAB	4.0	1.9	2.2	4.3	7.7	3 Lugs	12	64, 98, H36, H42	TE
	1625	460	8331	\$257	SAB	4.0	.95	2.2	4.3	7.7	3 Lugs	13	98, 64, H36, H42	TE
	1625	460	6138	\$288	SAB	5.0	0.90	3.1	4.8	7.9	Stud	19	64, 98	CO
	1625	575	1312	\$250	SAB	5.0	0.7	3.1	4.8	7.9	Stud	19	64, 98	
1/3	1625	208-230	6127	\$264	SAB	4.0	2.2	1.8	5.8	8.7	Resilient	15	98, 64, H45	CO
	1625	208-230	7232	\$290	SAB	6.0	2.9	3.7	4.6	9.3	Resilient	23	64, H35	HR
	1075/2	208-230	1354	\$239	Ball	7.5	2.0	3.1	4.8	8.4	3 Lugs	11	H36	
1/2	1725	208-230	644	\$250	Ball	5.0	2.7	3.5	5.6	9.1	Stud	15	98, H18, H36	HU
	1100	208-230/460	4941	\$350	Ball	12.5	2.8/1.5	4.5	5.9	11.4	Resilient	16	64, H18, H36	-

CO = Copeland

HU = Hussmann

HR = Hill Refrigeration

TE = Tecumseh

TY = Tyler

Note 64: Capacitor Included

Note 98: 50/60 Hz

Note H4: 2-1/4" hub rings

Note H18: Conduit box

Note H35: Open Air Over

Note H36: Open Drip Proof

Note H42: Shaft Down

Note H45: Totally Enclosed, Air Over