


# Permanent Split Capacitor Direct Drive Fan Single Shaft 5.0" Diameter, Open Air Over




## APPLICATIONS:

Designed to meet manufacturer's requirements for direct drive fan and blowers.

## FEATURES:

- Reversible Unless Noted
- Sleeve Bearings have All Angle Thrust System
- Suitable for Use With 370V Capacitors
- Continuous Duty, Air Over
- 24" Line Leads Unless Otherwise Noted
- Automatic Reset Thermal Overload Protector
- Connection & Capacitor Information Furnished in Nameplate Data
- **Discount Symbol: DS-3HAC**



## Permanent Split Capacitor, 5.0" Diameter, Stud or Hub Ring Mount (2.5")

HP	RPM/ Spds.	Voltage	Catalog Number	List	Bearings	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Stud YM	Ship Wt.	Notes
1/5	1075/3	203-230	8952	\$206	SAB	5.0	1.6	4.0	5.3	4.9	9.9	N/A	11	
	1075/4	115	1268	\$150	SAB	4.0	3.4	3.5	4.6	4.1	8.7	1	10	98
1/4	1050/3	115	1390	\$160	SAB	7.5	2.8	4.0	4.9	4.3	8.9	1	12	H24
	1050/3	208-230	1391	\$163	SAB	7.5	1.5	4.0	4.9	4.3	8.9	1	12	H24
1/3	1075/3	115	8955	\$136	SAB	15.0	3.8	4.0	5.1	-	10.2	.75	8	

Note 98: 50/60 Hz

Note H24: Hub Rings not included