

Pressure Switches

MARS SERIES **339**



Fixed Setting Pressure Controls

High Pressure Cut-Outs

MARS2 offers the most complete line of high pressure cut-outs available.

Specifications:

- Contacts rated at 6 amps, 24-240 volts
- 1/4" female flare S.A.E. mounting
- 18" leads

Features:

- Tamper proof construction
- Direct mounting on tubing
- UL & CSA recognized

High Pressure Cut-Outs, Automatic Reset, Open On Pressure Rise, Normally Closed

MARS2 NO.	MODEL NO.	OPENING PRESSURE	RESET PRESSURE
33954	PS80-K1-0336-250-150	250	150
33910	PS80-K1-0339-275-195	275	195
33955	PS80-K1-0341-300-200	300	200
33913	PS80-K1-0346-325-230	325	230
33916	PS80-K1-0348-350-250	350	245
33956	PS80-K1-0348-350-250	350	250
33919	PS80-K1-0353-375-265	375	265
33957	PS80-K1-0357-400-200	400	200
33922	PS80-K1-0358-400-280	400	280
33958	PS80-K1-0359-400-300	400	300
33925	PS80-K1-0360-425-300	425	300
33959	PS80-K1-0363-450-250	450	250
33960*	PS80-01-0926-420-320	420	320
33967*	PS80-01-0927-400-300	400	300

* With cap tube fitting

MARS2