

Series 250G



Output Options:

Model 250G-0xx	1-5 Vout
Model 250G-1xx	Reserved
Model 250G-2xx	Reserved
Model 250G-3xx	4 – 20 mA (2 wire)
Model 250G-4xx	Reserved
Model 250G-5xx	Special Instructions

Cable Length Options:

Model 250G-x0x	Reserved
Model 250G-x1x	Reserved
Model 250G-x2x	24.0” Standard
Model 250G-x3x	Reserved
Model 250G-x4x	Reserved
Model 250G-x5x	Special Instructions

Calibration Pressure Options (Full Scale):

Model 250G-xx1	100 PSI
Model 250G-xx2	250 PSI
Model 250G-xx3	500 PSI
Model 250G-xx4	1,000 PSI
Model 250G-xx5	Special
Model 250G-xx6	2,500 PSI
Model 250G-xx7	5,000 PSI
Model 250G-xx8	10,000 PSI

Max Non-Destructive Over Pressure

200 PSI
500 PSI
1,000 PSI
2,000 PSI
5,000 PSI
10,000 PSI
20,000 PSI

Burst

500 PSI
1250 PSI
2,500 PSI
5,000 PSI
12,500 PSI
20,000 PSI
20,000 PSI

Example: Requirement is for 4-20 mA out with pressure range of 0 - 200 PSI with standard 24 inch cable

Order = Series 250G-322, Description: 4-20 mA out, 250 PSI, standard cable = 24”