



#16 GREEN GROUND LEAD TO BE 9.000±.250 BETWEEN CENTERS OF TERMS. TERM TO FIT .250 SCREW ATTACHED UNDER THIS STATOR SCREW NUT.

(2) #18 LEADS .062 THICK INSUL TO EXTEND BEYOND MOTOR:
 BLK= 63.000 +2-0
 WHT= 63.000 +2-0

NIDEC MOTOR CORPORATION 09-Nov-16

MODEL	REF	CUSTOMER	HP	VOLTS	AMPS	HZ	RPM	ROTATION	CUSTOMER PN
K55HXPZZ-7698		STANDARD	1/3B	208-230	3.5	50/60	1075	CW LEAD END	CAT NO. 6986

SHEET NUMBER	REV	REVISION RECORD FOR: ECO: E27191
1 OF 1	F	DELETED NOTE THE OBSOLETE
REVISION DATE		
09-NOV-16		

INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION

NIDEC MOTOR CORPORATION

ISSUED BY	REVIEWED BY	ENGINEER APPROVED
C.ALMAGUER	H.NAVARRO	H.NAVARRO

TITLE	CODE	ITEM NO.	SIZE
ASSEMBLED VIEW	V01	754161	A