



GROUND LEAD (1): GREEN; 16 AWG; .031 (PVC) INSULATION; TO BE 3.000 ±.250 BETWEEN CENTERS OF TERMS.; #10 RING TERMINATION

CONNECTIONS:  
 LINE BETWEEN BLACK LEADS  
 CUSTOMER CIRCUIT BETWEEN BROWN LEAD  
 TO REVERSE INTERCHANGE RED & BLACK

NIDEC MOTOR CORPORATION 11-Oct-12

MODEL	REF	CUSTOMER	HP	VOLTS	AMPS	HZ	RPM	ROTATION	CUSTOMER PN
S63JXTSM-7998		STANDARD	1/4	208-230	2.9	60	1140	CCW LEAD END REV	7998

SHEET NUMBER	REV	REVISION RECORD FOR:	ITEM NO.
1 OF 1	E	UPDATED "ENGINEER APPROVED" B. GAITAN	C6408-00
REVISION DATE			
11-OCT-12			

INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION

**NIDEC MOTOR CORPORATION**

ISSUED BY	REVIEWED BY	ENGINEER APPROVED
E. VICENCIO	M. LARGENT	B. GAITAN

TITLE	CODE	ITEM NO.	SIZE
ASSEMBLED VIEW	V01	756658	A