


12 LEADS # 18, .031 THICK INSUL TO EXTEND BEYOND MOTOR 6.000 +2 -0 MEASURING FROM INTERNAL CONNECTION BOX. LEADS TO BE NUMBERED 1 THRU 12 AND SKINNED .750

1/2-14 NPSM THREAD CONDUIT HOLE



LOW VOLTAGE SERIES PARALLEL HIGH VOLTAGE SERIES

S.F.
1.15/1.0

NOTE: SHAFT KEY TAPED TO MOTOR

NIDEC MOTOR CORPORATION 14-Feb-12

MODEL	REF	CUSTOMER	HP	VOLTS	AMPS	HZ	RPM	ROTATION	CUSTOMER PN
P63SYFGE-4116		USEM	2.0	208-230/460 190/380	6.2/3.1	60/50	1725/1425	REVERSIBLE	SV2E2D

SHEET NUMBER 1 OF 1	REV D	REVISION RECORD FOR: C4997-13	
		UPDATED BACKGROUND FROM EMERSON TO NIDEC	
REVISION DATE			
14-FEB-12			

INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION

NIDEC MOTOR CORPORATION

ISSUED BY A. SANCHEZ	REVIEWED BY J.I. SALAZAR	ENGINEER APPROVED J.I. SALAZAR
-------------------------	-----------------------------	-----------------------------------

TITLE ASSEMBLED VIEW		CODE V01	ITEM NO. 758070	SIZE A
-------------------------	--	-------------	--------------------	-----------