


(3) .250 INSULATED STRAIGHT TYPE Q.C. TERMINALS WITH INSUL. GRIP AMP ULTRA POD #521367-2 OR EQUIVALENT

3 LEADS #18, 2/64 THICK INSUL. TO EXTEND THROUGH CONDUIT FITTING: PUR=35.000 +2 -0, BLK=35.000 +2 -0 ORG=35.000 +2 -0



MOTOR MOUNTED IN SHAFT-DOWN POSITION

NIDEC MOTOR CORPORATION 13-Nov-12

MODEL	REF	CUSTOMER	HP	VOLTS	AMPS	HZ	RPM	ROTATION	CUSTOMER PN
K55HXDVC-1267	A33566	WHOLESALE HAC	1/4	208-230	1.7	60	825	C.CW. LEAD END	LX7931

SHEET NUMBER	REV	REVISION RECORD FOR: C6402-01
1 OF 1	B	UPDATED ENGINEER APPROVED TO B. GAITAN
REVISION DATE		
13-NOV-12		

INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION

NIDEC MOTOR CORPORATION

ISSUED BY	REVIEWED BY	ENGINEER APPROVED	REV.
R. MORALES	M. LARGENT	B. GAITAN	B

TITLE	CODE	ITEM NO.	SIZE
ASSEMBLED VIEW	V01	789068	A