

GREEN GROUND SCREW

SHAFT KEY TAPED TO MOTOR.

WARNING LABEL

NAMEPLATE

90°


TOP

SPLIT IN MTG. RING

CONDUIT PLUG 1/2-14 NPS THR'D

STARTING SWITCH END

GROUND LEAD (1): GREEN; 16 AWG; 2/64" (PVC) INSULATION; TO BE 6.000±.250 BETWEEN CENTERS OF TERMS.; *10 RING TERMINATION.



TO REVERSE ROTATION INTERCHANGE RED & BLK LEADS

NIDEC MOTOR CORPORATION 12-Oct-12

MODEL	REF	CUSTOMER	HP	VOLTS	AMPS	HZ	RPM	ROTATION	CUSTOMER PN
S63JFY-8120		USEM	1/4	115	5.5	60	1140	CW/CCW	D14B3N9

SHEET NUMBER	REV	REVISION RECORD FOR: JC 67909
1 OF 1	--	CREATED DRAWING
REVISION DATE		
10-OCT-12		

INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION

ALL DIMENSIONS ARE FOR REFERENCE ONLY UNLESS TOLERANCE IS GIVEN

NIDEC MOTOR CORPORATION

ISSUED BY	REVIEWED BY	ENGINEER APPROVED
A. SAUCEDO	T. BOSSALLER	T. BOSSALLER

TITLE
ASSEMBLED VIEW

CODE
V01

ITEM NO.
794142

SIZE
A